











PRODUCT CHART

STRAIGHT BLADE CONFIGURATIONS

AMPS	POLES/ WIRES	VOLTAGE	NEMA CONFIG.	AC HP RATING	APPLICATION ENVIRONMENT	CONNECTOR	PLUG	RECEPTACLE		FLANGED OUTLET		DUST- RESISTANT INLET	DUST- RESISTANT OUTLET	CAT. Pg.
								SINGLE	DUPLEX	INLET	OUTLET			
15A	2P 3W	125V		.5	Spec. Grade	5269*	5266*	5251	5252	5278*	5279*	5278DRI	5279DRO	5
					Corrosion-Rst.	5269CRS	5266CRS	5361CRS	-	-	-	-	-	21
					All Black	5269BL*	5266BL*	-	-	5278BL	5279BL	-	-	25
					Hosp. Grade	8219	8215	8210	8200	-	-	-	-	28
						8219T	8215T	-	-	-	-	-	-	28
		Isolated Grnd.	-	5266IG	5261IG	5262IG	-	-	-	-	29			
		250V		1.5	Spec. Grade	5669*	5666*	5651	5662	5678*	5679*	5678DRI	5679DRO	5
					Hosp. Grade	8619	8615	-	8600	-	-	-	-	28
						8619T	8615T	-	-	-	-	-	-	28















NEMA LOCKING CONFIGURATIONS

AMPS	POLES/ WIRES	VOLTAGE	NEMA CONFIG.	AC HP RATING	APPLICATION ENVIRONMENT	CONNECTOR	PLUG	RECEPTACLE		FLANGED OUTLET		DUST- RESISTANT INLET	DUST- RESISTANT OUTLET	CAT. Pg.		
								SINGLE	DUPLEX	INLET	OUTLET					
15A	2P 3W	125V		.5	Spec. Grade	4729*	4720*	4710	4700	4716*	4715*	4716DRI	4715DRO	7		
					Corrosion-Rst.	4729CRS	4720CRS	4710CRS	4700CRS	-	-	-	-	21		
					All Black	4729BL*	4720BL*	-	-	-	-	-	-	25		
					Isolated Grnd.	-	4720IG	4710IG	4700IG	-	-	-	-	29		
		250V		2	Spec. Grade	4579*	4570*	4560	4550	4586*	4585*	4586DRI	4585DRO	7		
					All Black	4579BL*	4570BL*	-	-	-	-	-	-	25		
					Isolated Grnd.	-	-	4560IG	4550IG	-	-	-	-	29		
		277V		2	Spec. Grade	4779	4770	4760	4750	4786*	4785*	4786DRI	4785DRO	7		
		20A	2P 3W	125V		1	Spec. Grade	205C*	205P*	205R*	-	205FI*	205FO*	-	-	11
							Corrosion-Rst.	205CCRS	205PCRS	205RCRS	-	-	-	-	21	
All Black	205CBL*						205PBL*	-	-	205FIBL	205FOBL	-	-	25		
Isolated Grnd.	-						205PIG	205RIG	-	-	-	-	29			
250V				2	Spec. Grade	206C*	206P*	206R*	-	206FI*	206FO*	-	-	11		
					All Black	206CBL*	206PBL*	-	-	-	-	-	25			
					Isolated Grnd.	-	206PIG	206RIG	-	-	-	-	29			
277V				2	Spec. Grade	207C*	207P*	207R*	-	207FI*	207FO*	-	-	11		
480V				5	Spec. Grade.	208C*	208P*	208R*	-	208FI*	208FO*	-	-	11		
600V				-	Spec. Grade	209C	209P	209R	-	209FI	209FO	-	-	11		

*Also available with .CN option: Combination Slot & Robertson Head Screws

PRODUCT CHART




NEMA LOCKING CONFIGURATIONS

AMPS	POLES/ WIRES	VOLTAGE	NEMA CONFIG.	AC HP RATING	APPLICATION ENVIRONMENT	CONNECTOR	PLUG	RECEPTACLE SINGLE	FLANGED		CATALOG PAGE
									INLET	OUTLET	
20A	3P 4W	125/250		2(1)	Spec. Grade	2014C	2014P	2014R	2014FI	2014FO	11
					All Black	2014CBL	2014PBL	-	2014FIBL	-	25
		3Ø 250		3	Spec. Grade.	2015C	2015P	2015R	2015FI	2015FO	11
		3Ø 480		5	Spec. Grade	2016C	2016P	2016R	2016FI	2016FO	11
	4P 5W	3Ø Y 120/208		2	Spec. Grade	2021C	2021P	2021R	2021FI	2021FO	11
					Spec. Grade	2022C	2022P	2022R	2022FI	2022FO	11
					Spec. Grade	2023C	2023P	2023R	2023FI	2023FO	11
		3Ø Y 277/480		5	Spec. Grade	2022C	2022P	2022R	2022FI	2022FO	11
		3Ø Y 347/600		-	Spec. Grade	2023C	2023P	2023R	2023FI	2023FO	11
30A	2P 3W	125V		2	Spec. Grade	305C*	305P*	305R*	305FI*	305FO*	12
					Corrosion-Rst.	305CCRS	305PCRS	305RCRS	-	-	21
					All Black	305CBL*	305PBL*	-	-	-	25
					Isolated Grnd.	-	305PIG	305RIG	-	-	29
		250V		2	Spec. Grade	306C*	306P*	306R*	306FI*	306FO*	12
					Corrosion-Rst.	306CCRS	306PCRS	306RCRS	-	-	21
	All Black				306CBL*	306PBL*	-	-	-	25	
	Isolated Grnd.				-	306PIG	306RIG	-	-	29	
	3P4W	125/250		2	Spec. Grade	3014C	3014P	3014R	3014FI	3014FO	12
					All Black	3014CBL	3014PBL	-	3014FIBL	-	25
		3Ø 250		3	Spec. Grade	3015C	3015P	3015R	3015FI	3015FO	12
					Spec. Grade.	3016C	3016P	3016R	3016FI	3016FO	12
		3Ø 480		10	Spec. Grade	3016C	3016P	3016R	3016FI	3016FO	12
					Spec. Grade	3016C	3016P	3016R	3016FI	3016FO	12
	4P 5W	3Ø Y 120/208		3	Spec. Grade	3021C	3021P	3021R	3021FI	3021FO	12
					Spec. Grade	3022C	3022P	3022R	3022FI	3022FO	12
					Spec. Grade	3023C	3023P	3023R	3023FI	3023FO	12
		3Ø Y 277/480		10	Spec. Grade	3022C	3022P	3022R	3022FI	3022FO	12
	3Ø Y 347/600		-	Spec. Grade	3023C	3023P	3023R	3023FI	3023FO	12	













*Also available with .CN option: Combination Slot & Robertson Head Screws

PRODUCT CHART

Non-NEMA Locking Configurations

AMPS	POLES/ WIRES	VOLTAGE	Non-NEMA CONFIG.	APPLICATION ENVIRONMENT	CONNECTOR	PLUG	RECEPTACLE SINGLE	FLANGED		CATALOG PAGE
								INLET	OUTLET	
20A	3P 3W	125/250	 Replacement use only	Spec. Grade	7314C	9965C	7310B	3325C	3326C	11
	4P 4W	3Ø Y 120/208	 Replacement use only	Spec. Grade	7413C	7411C	7410B	7408C	7409C	11
30A	4P 4W	3Ø Y 120/208	 Replacement use only	Spec. Grade	3433C	3431C	3430	3434C	3435C	12

50 AMP DEVICES

AMPS	POLES/ WIRES	VOLTAGE	CONFIGURATION	APPLICATION ENVIRONMENT	CONNECTOR	PLUG	RECEPTACLE SINGLE	FLANGED INLET	CATALOG PAGE	
50A	2P 3W	125	 Calif. Standard	Spec. Grade	CS6360N	CS6361N	CS6370	CS6377	17	
			 SS1-50	Corrosion-Rst.	6360CRNS	6361CRNS	6370CRS	6377CRS	21	
		250	 Calif. Standard	Spec. Grade	CS8264N	CS8265N	CS8269	CS8275	17	
			 Replacement use only	Spec. Grade	3762N	3763N	3771	3777	17	
			480	 Calif. Standard	Spec. Grade	CS8464N	CS8465N	CS8469	CS8475	17
				 Replacement use only	Spec. Grade	CS6364N	CS6365N	CS6369	CS6375	17
	3P 4W	125/250	 Calif. Standard	Spec. Grade	6364CRNS	6265CRNS	6369CRS	6375CRS	21	
			 SS2-50	Corrosion-Rst.	6364CRNS	6265CRNS	6369CRS	6375CRS	21	
		3Ø 250	 Calif. Standard	Spec. Grade	CS8364N	CS8365N	CS8369	CS8375	17	
			 Replacement use only	Spec. Grade	3764N	3765N	3769	3775	17	
			250DC/600 AC	 Replacement use only	Spec. Grade	7764N	7765N	-	7958	17
				 Calif. Standard	Spec. Grade	CS8164N	CS8165N	CS8169	CS8175	17

60 AMP DEVICES

AMPS	POLES/ WIRES	VOLTAGE	CONFIGURATION	APPLICATION ENVIRONMENT	RIGHT ANGLE CONNECTOR	RIGHT ANGLE HEADER	STRAIGHT MOUNT HEADER	CATALOG PAGE
60A	2P 3W	50 DC	Three Industry Standard .550 Centerline- Space Pins	Printed Circuit Boards	603RAC	603RAH	603STH	36