

Carol Brand Cable

Super Vu-Tron® Entertainment Industry and Stage Lighting Cable

105°C 600 Volt UL Type SC and CSA Type PPC

--One of the most popular cables in the power distribution market--

Product Construction:

Conductor:

- 8 through 4/0 AWG fully annealed stranded bare copper per ASTM B-172

Jacket:

- Super Vu-Tron® 105°C, Black
- Temperature Range: -50°C to +105°C

Jacket Marking:

- CAROL (SIZE) (UL) 600 BOLT TYPE SC (-50°C to +105°C) OIL RES 60°C MAX. AMPS NEC TABLE 400-5 (B) FOR 90°C OUTDOOR – CSA TYPE PPC 105°C VOLT FT5

Applications:

- Portable Power Systems
- Entertainment industry activities such as theatre, television, night clubs, motion pictures, mobile communication vans, spotlights and sound systems
- Other similar applications that would require temporary power

Features:

- Water resistant
- Sunlight resistant
- Designed to withstand severe environmental conditions
- Withstands exposure to oil, acids, alkalis, heat, flame, moisture and chemicals
- Meets or exceeds flame test requirements of MSHA, CSA and UL

Industry Approvals:

- UL Listed
- CSA Certified

Packaging:

- Lengths cut to order

- Tie Straps Available
- Cable Assemblies cut to length and built using cam-loks or advanced devices connectors
- Cable Assemblies can be banded
- We provide terminated tails
- Highly flexible and easy to roll at all temperatures

UL TYPE SC – CSA TYPE PPC – 600 VOLT						
CATALOG NUMBER	AWG SIZE	NOMINAL STRAND	NOMINAL OD INCHES	NOMINAL OD MM	APPROX. NET WEIGHT LBS/M ^s	CURRENT AMPS
01108	6	259 / 30	0.430	10.92	150	105
01107	4	418 / 30	0.475	12.06	210	140
01106	2	660 / 30	0.560	14.22	300	190
01105	1	836 / 30	0.580	14.73	365	220
01104	1/0	1056 / 30	0.635	16.13	440	260
01103	2/0	1320 / 30	0.665	16.89	555	300
01101	4/0	2090 / 30	0.780	19.81	805	405

Actual shipping weight may vary



www.jcustom.com

1-800-226-5657

Phone: (225)272-2210

Fax: (225) 272-2223

E-mail:

jcustomsupply@bellsouth.net



J Custom Supply, Inc.

10345 South Perdue

Baton Rouge, LA

70814