

Carol Brand Cable

Super Vu-Tron® Single Conductor Type W Extra – Flex

90°C 2000 Volt UL Listed

TYPE W – 2000 VOLT UL

CATALOG NUMBER	AWG SIZE	NOMINAL STRAND	NOMINAL OD INCHES	NOMINAL OD MM	APPROX. NET WEIGHT LBS/M ^s	CURRENT AMPS
80611*	8	162 / 30	0.440	11.18	150	80
80621	6	260 / 30	0.510	12.95	205	105
80631	4	418 / 30	0.565	14.35	260	140
80641	2	778 / 30	0.650	16.51	380	190
80651	1	836 / 30	0.730	18.54	480	220
80661*	1/0	1056 / 30	0.750	19.05	535	260
80671	2/0	1248 / 30	0.800	20.32	655	300
80681*	3/0	1672 / 30	0.855	21.72	755	350
80691	4/0	2054 / 30	0.980	24.89	990	405
80701*	250 MCM	2496 / 30	1.000	25.40	1150	455

* Non-stock item; minimum quantity purchase required

^s Actual shipping weight may vary

Product Construction:

Conductor:

- 8 through 250 MCM fully annealed stranded bare copper per ASTM B-172

Insulation:

- Premium grade 90°C EPDM

Jacket:

- Super Vu-Tron® 90°C, Black
- Temperature Range: -40°C to +90°C

Jacket Marking:

- CAROL SUPER VU-TRON® TYPE W PORTABLE POWER CABLE (SIZE) 2000V 90°C DRY AND WATER RESISTANT 75°C SUN RES (UL) P-7K-123049

Applications:

- Portable Power Systems
- Entertainment industry activities such as theatre, television, night clubs, motion pictures, mobile communication vans, spotlights and sound systems
- Other similar applications that would require temporary power

Features:

- Water resistant
- Sunlight resistant
- Designed to withstand severe environmental conditions
- Withstands exposure to oil, acids, alkalis, heat, flame, moisture and chemicals
- Meets or exceeds flame test requirements of MSHA, ICEA and UL

Industry Approvals:

- UL Listed
- MSHA Approved

Packaging:

- Lengths cut to order



www.jcustom.com

1-800-226-5657

Phone: (225)272-2210

Fax: (225) 272-2223

E-mail:

jcustomsupply@bellsouth.net



J Custom Supply, Inc.

10345 South Perdue

Baton Rouge, LA

70814