

## NEMA WIRING DEVICES



5266-CB  
Male Plug



5269-CB  
Female Connector



5352-R  
Duplex Receptacle



5278-C  
Flanged Inlet



5279-C  
Flanged Inlet

Poles/ Wires	AC Volts	NEMA Config	Male Plug	Female Connector	Single Receptacle	Duplex Receptacle	Flanged Inlet	Flanged Outlet
<b>15 Amp Devices - Straight Blade</b>								
2P3W	125	5-15	5266-CB	5269-CB	5251	5252	5278-C	5279-C
2P3W	250	6-15	5666-C	5669-C	5621	5652	15678-C	15679-C
<b>15 Amp Devices - Locking</b>								
2P3W	125	L5-15	4720-CB	4729-CB	4710	4700	4716-C	4715-C
2P3W	250	L6-15	4570-CB	4570-CB	4560	4550	4586-C	4585-C
<b>20 Amp Devices - Straight Blade</b>								
2P3W	125	5-20	5366-C	5369-C	5351	5352	15378-C	15379-C
2P3W	250	6-20	5466-C	5469-C	5421	5452	5478-C	5479-C
<b>20 Amp Devices - Locking</b>								
2P3W	125	L5-20	2311-CB	2313-CB	2310		2315	2316
2P3W	250	L6-20	2321	2323	2310		2325	2326
3P3W	125/250	Non-Nema "Old Style"	9965-C	7314-C	2510		3325-C	3326-C
3P4W	125/250	L14-20	2411	2413	2410		2415	2416
3P4W	3Ø250	L15-20	2421	2423	2420		2425	2426
4P5W	3ØY120/208	L21-20	2511	2513	2510		2515	2516
<b>30 Amp Devices - Straight Blade</b>								
2P3W	125	5-30	P530DF	C530DF	5371			
2P3W	250	6-30	P630DF	C630DF	5372			
<b>30 Amp Devices - Locking</b>								
2P3W	125	L5-30	2611	2613	2610		2615	2616
2P3W	250	L6-30	2621	2623	2620		2625F	2626F
3P4W	125/250	L14-30	2711	2713	2710		2715	2716
3P4W	3Ø250	L15-30	2721	2723	2720		2725	2726
4P5W	3ØY120/208	L21-30	2811	2813	2810		2815	2816
<b>50 Amp Devices - Straight Blade</b>								
3P4W	125	5-50	P550DF	C550DF	5373			
3P4W	125/250	14-50	PL1450DF	CL1450DF	279			
<b>50 Amp Devices - Locking</b>								
3P4W	125	CS Series	CS63-61C	CS63-60C	CSS63-70	CS63-77		
3P4W	125/250	CS Series	CS63-65C	CS63-64C	CS63-69	CS63-75		
3P4W	3Ø250	CS Series	CS83-65C	CS83-64C	CS83-69	CS83-75		
3P4W	480	CS Series	CS81-65C	CS81-64C	CS81-69	CS81-75		
<b>60 Amp Devices - Straight Blade</b>								
3P4W	3Ø250	15-60	P1560YP	C1560YP	8460-A			